



Essential SmartBright Solar Flood Light

BVC080 LED6/765

Solar flood lighting DIY kit with lithium ferro phosphate battery built in the luminaire, Remote controller and installation accessories included. IP 65 ABS plastic construction for sturdiness and long life. Available in 600, 900 and 1500 Lumens

Warnings and Safety

- This product includes rechargeable batteries which must be adequately charged under sunlight before use.

Product data

General information		Configurability	
Driver included	Yes	Configurable	
Optical cover/lens type	Polycarbonate	Mechanical and housing	
Control interface	IR remote	Overall length	150 mm
Warranty period	1 years	Overall width	48 mm
Material	Acrylonitrile-butadiene-styrene	Overall height	120 mm
Operating and electrical		Approval and application	
Battery type	Lithium Ferro Phosphate	Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Battery ampere hour	5 Ah	Initial performance (IEC compliant)	
Battery voltage	3.2 V	Initial luminous flux (system flux)	600 lm
Panel type	Poly crystalline	Initial LED luminaire efficacy	150 lm/W
Panel voltage	5 V	Init. Corr. Color Temperature	6500 K
Panel peak wattage	5 W	Init. Color Rendering Index	>70
Charge controller type	PWM	Application conditions	
Controls and dimming		Ambient temperature range	0 to +45 °C
Dimmable	Yes	Solar dimming profile	As per remote controller


Essential SmartBright Solar Flood Light

Battery location	Inside luminaire
Product data	
Full product code	692382864894799
Order product name	BVC080 LED6/765
EAN/UPC - Product	6923828648947
Order code	911401827202

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	911401827202
Net Weight (Piece)	1.210 kg

IP65

Dimensional drawing



BVC080 LED6/765





Essential SmartBright Solar Flood Light

BVC080 LED9/765

Solar flood lighting DIY kit with lithium ferro phosphate battery built in the luminaire, Remote controller and installation accessories included. IP 65 ABS plastic construction for sturdiness and long life. Available in 600, 900 and 1500 Lumens

Warnings and Safety

- This product includes rechargeable batteries which must be adequately charged under sunlight before use.

Product data

General information		Configurability	Configurable
Driver included	Yes		
Optical cover/lens type	Polycarbonate	Mechanical and housing	
Control interface	IR remote	Overall length	183 mm
Warranty period	1 years	Overall width	48 mm
Material	Acrylonitrile-butadiene-styrene	Overall height	143 mm
Operating and electrical		Approval and application	
Battery type	Lithium Ferro Phosphate	Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Battery ampere hour	5 Ah	Initial performance (IEC compliant)	
Battery voltage	3.2 V	Initial luminous flux (system flux)	900 lm
Panel type	Poly crystalline	Initial LED luminaire efficacy	150 lm/W
Panel voltage	5 V	Init. Corr. Color Temperature	6500 K
Panel peak wattage	7 W	Init. Color Rendering Index	>70
Charge controller type	PWM	Application conditions	
Controls and dimming		Ambient temperature range	0 to +45 °C
Dimmable	Yes	Solar dimming profile	As per remote controller


Essential SmartBright Solar Flood Light

Battery location	Inside luminaire
Product data	
Full product code	692382864895499
Order product name	BVC080 LED9/765
EAN/UPC - Product	6923828648954
Order code	911401827302

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	10
Material Nr. (12NC)	911401827302
Net Weight (Piece)	1.390 kg

IP65

Dimensional drawing



BVC080 LED9/765





Essential SmartBright Solar Flood Light

BVC080 LED15/765

Solar flood lighting DIY kit with lithium ferro phosphate battery built in the luminaire, Remote controller and installation accessories included. IP 65 ABS plastic construction for sturdiness and long life. Available in 600, 900 and 1500 Lumens

Warnings and Safety

- This product includes rechargeable batteries which must be adequately charged under sunlight before use.

Product data

General information	
Driver included	Yes
Optical cover/lens type	Polycarbonate
Control interface	IR remote
Warranty period	1 years
Material	Acrylonitrile-butadiene-styrene
Operating and electrical	
Battery type	Lithium Ferro Phosphate
Battery ampere hour	10 Ah
Battery voltage	3.2 V
Panel type	Poly crystalline
Panel voltage	5 V
Panel peak wattage	10 W
Charge controller type	PWM
Controls and dimming	
Dimmable	Yes

Configurability	Configurable
Mechanical and housing	
Overall length	220 mm
Overall width	53 mm
Overall height	170 mm
Approval and application	
Ingress protection code	IP65 [Dust penetration-protected, jet-proof]
Initial performance (IEC compliant)	
Initial luminous flux (system flux)	1500 lm
Initial LED luminaire efficacy	150 lm/W
Init. Corr. Color Temperature	6500 K
Init. Color Rendering Index	>70
Application conditions	
Ambient temperature range	0 to +45 °C
Solar dimming profile	As per remote controller


Essential SmartBright Solar Flood Light

Battery location	Inside luminaire
Product data	
Full product code	692382864896199
Order product name	BVC080 LED15/765
EAN/UPC - Product	6923828648961
Order code	911401827402

Numerator - Quantity Per Pack	1
Numerator - Packs per outer box	5
Material Nr. (12NC)	911401827402
Net Weight (Piece)	1.730 kg

IP65

Dimensional drawing



BVC080 LED15/765

