



# PL-C 2-PIN

## PL-C 26W/865/2P 1CT/5X10BOX

PL-C new shape is an efficient and effective medium wattage fluorescent lamp, used in general downlights for retail, hospitality and office applications. The 2 PIN version is designed for electromagnetic gear and is provided with plug in/pull out lamp base. The 4 PIN version is designed for operation on electronic HF control gear with integrated pre-heat and is provided with a plug-in/pull-out lamp base.

### Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General Information		Color rendering index (CRI)	
Cap-Base	G24d-3		>80
Nominal lifetime	8,000 hour(s)	Operating and Electrical	
Light Technical		Power Consumption	26.5 W
Color Code	865 [CCT of 6500K]	Lamp Current (Nom)	325 mA
Luminous Flux	1,700 lm	Controls and Dimming	
Luminous Efficacy (rated) (Nom)	65 lm/W	Dimmable	Yes
Color Designation	Cool Daylight	Mechanical and Housing	
Chromaticity Coordinate X (Nom)	313	Bulb Shape	PL-C
Chromaticity Coordinate Y (Nom)	337		
Correlated Color Temperature (Nom)	6500 K		

## PL-C 2-PIN

### Approval and Application


Mercury (Hg) Content (Nom)	1.3
----------------------------	-----

### Product Data

Order product name	PL-C 26W/865/2P 1CT/5X10BOX
Full product name	PL-C 26W/865/2P 1CT/5X10BOX
Full product code	872016922872600
Order code	927812986501

Material Nr. (12NC)	927812986501
Numerator - Quantity Per Pack	1
Net Weight (Piece)	0.040 kg
EAN/UPC - Product/Case	8720169228726
Numerator - Packs per outer box	50
EAN/UPC - Case	8720169228740

### Dimensional drawing



Product	D (max)	D1 (max)	A	B
PL-C 26W/865/2P 1CT/5X10BOX	26 mm	26 mm	146.5 mm	169.5 mm





# PL-C 2-PIN

## PL-C 26W/840/2P 1CT/5X10BOX

PL-C new shape is an efficient and effective medium wattage fluorescent lamp, used in general downlights for retail, hospitality and office applications. The 2 PIN version is designed for electromagnetic gear and is provided with plug in/pull out lamp base. The 4 PIN version is designed for operation on electronic HF control gear with integrated pre-heat and is provided with a plug-in/pull-out lamp base.

### Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General Information		Color rendering index (CRI)	
Cap-Base	G24d-3		>80
Nominal lifetime	8,000 hour(s)	Operating and Electrical	
Light Technical		Power Consumption	26.5 W
Color Code	840 [CCT of 4000K]	Lamp Current (Nom)	325 mA
Luminous Flux	1,800 lm	Controls and Dimming	
Luminous Efficacy (rated) (Nom)	67 lm/W	Dimmable	No
Color Designation	Cool White (CW)	Mechanical and Housing	
Chromaticity Coordinate X (Nom)	380	Bulb Shape	PL-C
Chromaticity Coordinate Y (Nom)	380		
Correlated Color Temperature (Nom)	4000 K		

## PL-C 2-PIN

### Approval and Application

Mercury (Hg) Content (Nom) 1.3

### Product Data

Order product name PL-C 26W/840/2P 1CT/5X10BOX  
Full product name PL-C 26W/840/2P 1CT/5X10BOX  
Full product code 872016922854200  
Order code 927812984001

Material Nr. (12NC) 927812984001

Numerator - Quantity Per Pack 1


Net Weight (Piece) 0.040 kg

EAN/UPC - Product/Case 8720169228542

Numerator - Packs per outer box 50

EAN/UPC - Case 8720169228566

### Dimensional drawing



Product	D (max)	D1 (max)	A	B
PL-C 26W/840/2P 1CT/5X10BOX	26 mm	26 mm	146.5 mm	169.5 mm





# PL-C 2-PIN

## PL-C 18W/830/2P 1CT/5X10BOX

PL-C new shape is an efficient and effective medium wattage fluorescent lamp, used in general downlights for retail, hospitality and office applications. The 2 PIN version is designed for electromagnetic gear and is provided with plug in/pull out lamp base. The 4 PIN version is designed for operation on electronic HF control gear with integrated pre-heat and is provided with a plug-in/pull-out lamp base.

### Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General Information		Color rendering index (CRI)	
Cap-Base	G24d-2		>80
Nominal lifetime	8,000 hour(s)	Operating and Electrical	
Light Technical		Power Consumption	18.3 W
Color Code	830 [CCT of 3000K]	Lamp Current (Nom)	220 mA
Luminous Flux	1,200 lm	Controls and Dimming	
Luminous Efficacy (rated) (Nom)	67 lm/W	Dimmable	No
Color Designation	Warm White (WW)	Mechanical and Housing	
Chromaticity Coordinate X (Nom)	440	Bulb Shape	PL-C
Chromaticity Coordinate Y (Nom)	403		
Correlated Color Temperature (Nom)	3000 K		

## PL-C 2-PIN

### Approval and Application

Mercury (Hg) Content (Nom) 1.3

### Product Data

Order product name PL-C 18W/830/2P 1CT/5X10BOX  
Full product name PL-C 18W/830/2P 1CT/5X10BOX  
Full product code 872016922710100  
Order code 927812783001

Material Nr. (12NC) 927812783001

Numerator - Quantity Per Pack 1


Net Weight (Piece) 0.040 kg

EAN/UPC - Product/Case 8720169227101

Numerator - Packs per outer box 50

EAN/UPC - Case 8720169227125

### Dimensional drawing



Product	D (max)	D1 (max)	A	B
PL-C 18W/830/2P 1CT/5X10BOX	26 mm	26 mm	127.5 mm	150.5 mm





# PL-C 2-PIN

## PL-C 18W/827/2P 1CT/5X10BOX

PL-C new shape is an efficient and effective medium wattage fluorescent lamp, used in general downlights for retail, hospitality and office applications. The 2 PIN version is designed for electromagnetic gear and is provided with plug in/pull out lamp base. The 4 PIN version is designed for operation on electronic HF control gear with integrated pre-heat and is provided with a plug-in/pull-out lamp base.

### Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General Information		Color rendering index (CRI)	
Cap-Base	G24d-2		>80
Nominal lifetime	8,000 hour(s)	Operating and Electrical	
Light Technical		Power Consumption	18.3 W
Color Code	827 [CCT of 2700K]	Lamp Current (Nom)	220 mA
Luminous Flux	1,200 lm	Controls and Dimming	
Color Designation	Incandescent White	Dimmable	No
Luminous Efficacy (rated) (Nom)	67 lm/W	Mechanical and Housing	
Chromaticity Coordinate X (Nom)	463	Bulb Shape	PL-C
Chromaticity Coordinate Y (Nom)	420		
Correlated Color Temperature (Nom)	2700 K		

## PL-C 2-PIN

### Approval and Application

Mercury (Hg) Content (Nom) 1.3

### Product Data

Order product name PL-C 18W/827/2P 1CT/5X10BOX  
Full product name PL-C 18W/827/2P 1CT/5X10BOX  
Full product code 872016922692000  
Order code 927812782701

Material Nr. (12NC) 927812782701

Numerator - Quantity Per Pack 1


Net Weight (Piece) 0.040 kg

EAN/UPC - Product/Case 8720169226920

Numerator - Packs per outer box 50

EAN/UPC - Case 8720169226944

### Dimensional drawing



Product	D (max)	D1 (max)	A	B
PL-C 18W/827/2P 1CT/5X10BOX	26 mm	26 mm	127.5 mm	150.5 mm







# PL-C 2-PIN

## PL-C 13W/865/2P 1CT/5X10BOX

PL-C new shape is an efficient and effective medium wattage fluorescent lamp, used in general downlights for retail, hospitality and office applications. The 2 PIN version is designed for electromagnetic gear and is provided with plug in/pull out lamp base. The 4 PIN version is designed for operation on electronic HF control gear with integrated pre-heat and is provided with a plug-in/pull-out lamp base.

### Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General Information		Color rendering index (CRI)	
Cap-Base	G24d-1		>80
Nominal lifetime	8,000 hour(s)	Operating and Electrical	
Light Technical		Power Consumption	13.4 W
Color Code	865 [CCT of 6500K]	Lamp Current (Nom)	175 mA
Luminous Flux	840 lm	Controls and Dimming	
Luminous Efficacy (rated) (Nom)	62 lm/W	Dimmable	No
Color Designation	Cool Daylight	Mechanical and Housing	
Chromaticity Coordinate X (Nom)	313	Bulb Shape	PL-C
Chromaticity Coordinate Y (Nom)	337		
Correlated Color Temperature (Nom)	6500 K		

## PL-C 2-PIN

### Approval and Application

Mercury (Hg) Content (Nom) 1.3

### Product Data

Order product name PL-C 13W/865/2P 1CT/5X10BOX  
Full product name PL-C 13W/865/2P 1CT/5X10BOX  
Full product code 872016922602900  
Order code 927812586501

Material Nr. (12NC) 927812586501

Numerator - Quantity Per Pack 1


Net Weight (Piece) 0.040 kg

EAN/UPC - Product/Case 8720169226029

Numerator - Packs per outer box 50

EAN/UPC - Case 8720169226043

### Dimensional drawing



Product	D (max)	D1 (max)	A	B
PL-C 13W/865/2P 1CT/5X10BOX	26 mm	26 mm	112.5 mm	136 mm





# PL-C 2-PIN

## PL-C 13W/840/2P 1CT/5X10BOX

PL-C new shape is an efficient and effective medium wattage fluorescent lamp, used in general downlights for retail, hospitality and office applications. The 2 PIN version is designed for electromagnetic gear and is provided with plug in/pull out lamp base. The 4 PIN version is designed for operation on electronic HF control gear with integrated pre-heat and is provided with a plug-in/pull-out lamp base.

### Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General Information		Color rendering index (CRI)	
Cap-Base	G24d-1		>80
Nominal lifetime	8,000 hour(s)	Operating and Electrical	
Light Technical		Power Consumption	13.4 W
Color Code	840 [CCT of 4000K]	Lamp Current (Nom)	175 mA
Luminous Flux	900 lm	Controls and Dimming	
Luminous Efficacy (rated) (Nom)	67 lm/W	Dimmable	No
Color Designation	Cool White (CW)	Mechanical and Housing	
Chromaticity Coordinate X (Nom)	380	Bulb Shape	PL-C
Chromaticity Coordinate Y (Nom)	380		
Correlated Color Temperature (Nom)	4000 K		

## PL-C 2-PIN

### Approval and Application

Mercury (Hg) Content (Nom) 1.3

### Product Data

Order product name PL-C 13W/840/2P 1CT/5X10BOX  
Full product name PL-C 13W/840/2P 1CT/5X10BOX  
Full product code 872016922584800  
Order code 927812584001

Material Nr. (12NC) 927812584001

Numerator - Quantity Per Pack 1


Net Weight (Piece) 0.040 kg

EAN/UPC - Product/Case 8720169225848

Numerator - Packs per outer box 50

EAN/UPC - Case 8720169225862

### Dimensional drawing



Product	D (max)	D1 (max)	A	B
PL-C 13W/840/2P 1CT/5X10BOX	26 mm	26 mm	112.5 mm	136 mm





# PL-C 2-PIN

## PL-C 13W/830/2P 1CT/5X10BOX

PL-C new shape is an efficient and effective medium wattage fluorescent lamp, used in general downlights for retail, hospitality and office applications. The 2 PIN version is designed for electromagnetic gear and is provided with plug in/pull out lamp base. The 4 PIN version is designed for operation on electronic HF control gear with integrated pre-heat and is provided with a plug-in/pull-out lamp base.

### Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General Information		Color rendering index (CRI)	
Cap-Base	G24d-1		>80
Nominal lifetime	8,000 hour(s)	Operating and Electrical	
Light Technical		Power Consumption	13.4 W
Color Code	830 [CCT of 3000K]	Lamp Current (Nom)	175 mA
Luminous Flux	900 lm	Controls and Dimming	
Luminous Efficacy (rated) (Nom)	67 lm/W	Dimmable	No
Color Designation	Warm White (WW)	Mechanical and Housing	
Chromaticity Coordinate X (Nom)	440	Bulb Shape	PL-C
Chromaticity Coordinate Y (Nom)	403		
Correlated Color Temperature (Nom)	3000 K		

## PL-C 2-PIN

### Approval and Application

Mercury (Hg) Content (Nom)	1.3
----------------------------	-----

### Product Data

Order product name	PL-C 13W/830/2P 1CT/5X10BOX
Full product name	PL-C 13W/830/2P 1CT/5X10BOX
Full product code	872016922566400
Order code	927812583001

Material Nr. (12NC)	927812583001
---------------------	--------------

Numerator - Quantity Per Pack	1
-------------------------------	---


Net Weight (Piece)	0.040 kg
--------------------	----------

EAN/UPC - Product/Case	8720169225664
------------------------	---------------

Numerator - Packs per outer box	50
---------------------------------	----

EAN/UPC - Case	8720169225688
----------------	---------------

### Dimensional drawing



Product	D (max)	D1 (max)	A	B
PL-C 13W/830/2P 1CT/5X10BOX	26 mm	26 mm	112.5 mm	136 mm





# PL-C 2-PIN

## PL-C 13W/827/2P 1CT/5X10BOX

PL-C new shape is an efficient and effective medium wattage fluorescent lamp, used in general downlights for retail, hospitality and office applications. The 2 PIN version is designed for electromagnetic gear and is provided with plug in/pull out lamp base. The 4 PIN version is designed for operation on electronic HF control gear with integrated pre-heat and is provided with a plug-in/pull-out lamp base.

### Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General Information		Color rendering index (CRI)	
Cap-Base	G24d-1		>80
Nominal lifetime	8,000 hour(s)	Operating and Electrical	
Light Technical		Power Consumption	13.4 W
Color Code	827 [CCT of 2700K]	Lamp Current (Nom)	175 mA
Luminous Flux	900 lm	Controls and Dimming	
Luminous Efficacy (rated) (Nom)	67 lm/W	Dimmable	No
Color Designation	Incandescent White	Mechanical and Housing	
Chromaticity Coordinate X (Nom)	463	Bulb Shape	PL-C
Chromaticity Coordinate Y (Nom)	420		
Correlated Color Temperature (Nom)	2700 K		

## PL-C 2-PIN

### Approval and Application

Mercury (Hg) Content (Nom) 1.3

### Product Data

Order product name PL-C 13W/827/2P 1CT/5X10BOX

Full product name PL-C 13W/827/2P 1CT/5X10BOX

Full product code 872016922548000

Order code 927812582701

Material Nr. (12NC) 927812582701

Numerator - Quantity Per Pack 1


Net Weight (Piece) 0.040 kg

EAN/UPC - Product/Case 8720169225480

Numerator - Packs per outer box 50

EAN/UPC - Case 8720169225503

### Dimensional drawing



Product	D (max)	D1 (max)	A	B
PL-C 13W/827/2P 1CT/5X10BOX	26 mm	26 mm	112.5 mm	136 mm







# PL-C 2-PIN

## PL-C 10W/865/2P 1CT/5X10BOX

PL-C new shape is an efficient and effective medium wattage fluorescent lamp, used in general downlights for retail, hospitality and office applications. The 2 PIN version is designed for electromagnetic gear and is provided with plug in/pull out lamp base. The 4 PIN version is designed for operation on electronic HF control gear with integrated pre-heat and is provided with a plug-in/pull-out lamp base.

### Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General Information		Color rendering index (CRI)	
Cap-Base	G24d-1		>80
Nominal lifetime	8,000 hour(s)	Operating and Electrical	
Light Technical		Power Consumption	10.4 W
Color Code	865 [CCT of 6500K]	Lamp Current (Nom)	190 mA
Luminous Flux	560 lm	Controls and Dimming	
Luminous Efficacy (rated) (Nom)	55 lm/W	Dimmable	No
Color Designation	Cool Daylight	Mechanical and Housing	
Chromaticity Coordinate X (Nom)	313	Bulb Shape	PL-C
Chromaticity Coordinate Y (Nom)	337		
Correlated Color Temperature (Nom)	6500 K		

## PL-C 2-PIN

### Approval and Application

Mercury (Hg) Content (Nom) 1.3

### Product Data

Order product name PL-C 10W/865/2P 1CT/5X10BOX

Full product name PL-C 10W/865/2P 1CT/5X10BOX

Full product code 872016922530500

Order code 927812486501

Material Nr. (12NC) 927812486501

Numerator - Quantity Per Pack 1


Net Weight (Piece) 0.030 kg

EAN/UPC - Product/Case 8720169225305

Numerator - Packs per outer box 50

EAN/UPC - Case 8720169225329

### Dimensional drawing



Product	D (max)	D1 (max)	A	B
PL-C 10W/865/2P 1CT/5X10BOX	26 mm	26 mm	84 mm	107.5 mm





# PL-C 2-PIN

## PL-C 10W/827/2P 1CT/5X10BOX

PL-C new shape is an efficient and effective medium wattage fluorescent lamp, used in general downlights for retail, hospitality and office applications. The 2 PIN version is designed for electromagnetic gear and is provided with plug in/pull out lamp base. The 4 PIN version is designed for operation on electronic HF control gear with integrated pre-heat and is provided with a plug-in/pull-out lamp base.

### Warnings and Safety

- Use only with electromagnetic control gear
- Lamp light technical and electrical characteristics are influenced by operating conditions, i.e. lamp ambient temperature and operating position
- Dimming is not possible
- A lamp breaking is extremely unlikely to have any impact on your health. If a lamp breaks, ventilate the room for 30 minutes and remove the parts, preferably with gloves. Put them in a sealed plastic bag and take it to your local waste facilities for recycling. Do not use a vacuum cleaner.

### Product data

General Information		Color rendering index (CRI)	
Cap-Base	G24d-1		80
Nominal lifetime	8,000 hour(s)	Operating and Electrical	
Light Technical		Power Consumption	10.4 W
Color Code	827 [CCT of 2700K]	Lamp Current (Nom)	190 mA
Luminous Flux	600 lm	Controls and Dimming	
Luminous Efficacy (rated) (Nom)	60 lm/W	Dimmable	No
Color Designation	Incandescent White	Mechanical and Housing	
Chromaticity Coordinate X (Nom)	463	Bulb Shape	PL-C
Chromaticity Coordinate Y (Nom)	420		
Correlated Color Temperature (Nom)	2700 K		

## PL-C 2-PIN

### Approval and Application

Mercury (Hg) Content (Nom) 1.3

### Product Data

Order product name PL-C 10W/827/2P 1CT/5X10BOX

Full product name PL-C 10W/827/2P 1CT/5X10BOX

Full product code 872016922512100

Order code 927812482701

Material Nr. (12NC) 927812482701

Numerator - Quantity Per Pack 1


Net Weight (Piece) 0.030 kg

EAN/UPC - Product/Case 8720169225121

Numerator - Packs per outer box 50

EAN/UPC - Case 8720169225145

### Dimensional drawing



Product	D (max)	D1 (max)	A	B
PL-C 10W/827/2P 1CT/5X10BOX	26 mm	26 mm	84 mm	107.5 mm

